

J	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7618 www.jrsmith.com MEMBER OF: INSTITUTE FIELD				LOCATION	
	ROOFTOP PLANTING AREA DRAIN					
	Bronze Dome Covered w/Stainless Steel Mesh Screen Body with 3" Threaded Outlet Connection 3" Dia. (75) Standpipe Neoprene Gaskets Press Fit (30-40 Durometer) Seepage Holes (When Specified) Collar Can Be Used as Flashing Clamp When Required 6 (150) DIA 4 1/2 (115) 2" (51) 24 (610) (Unless Specified) 4 3/4 (120) Δ6 (150) Structural Slab 9 3/4 (250) DIA 12 (305) DIA A ΔSame for inside Caulk, NO-HUB & Speedi-Set®					
	A (Pipe Size) = 02(50), 03(75), 04(100), 05(125) or 06(150)					
1906	REGULARLY FURNISHED: Duco Cast Iron Upper Body with Bronze Flashing Clamp, Secured Bronze Dome with Stainless Steel Mesh Screen. Duco Cast Iron Lower Body with Combined Flashing Clamp, Perforated PVC Standpipe and Neoprene Isolation Gasket.					
	VARIATIONS: ☐ Fig. 1906C . . . CAULK Outlet ☐ Fig. 1906T . . . THREADED Outlet ☐ Fig. 1906Y . . . NO-HUB Outlet ☐ Sump Receiver -R ☐ Underdeck Clamp -C ☐ Vandal Proof Dome -U ☐ Solid Standpipe ☐ Roof Deck Plate -RDP OPTIONS: ☐ Cast Iron Standpipe ☐ Galvanized Cast Iron - G					
	NOTE: Dimensions shown in parentheses are in millimeters.					
	WEIGHT POUNDS VOLUME CUBIC FEET FIGURE NUMBER 1906					
FIGURE NUMBER	REV.	DATE	DESCRIPTION	BY	CKD. BY	
		JH 9-27-24 GF 3-15-23 F 2-14-23 4-12-16	Revised Variations Added ® to Speedi-Set Revised Reg. Furnished Revised Variations	HS KK KK TBW	CL CL CL BW	