

3001-Series	DRAWN BY: CR	CHECKED BY: KH	APPROVED BY: JM	DATE: 5-4-82	SCALE: NONE	SIZE: A	DRAWING NUMBER: S3001	Z																				
	JAY R. SMITH MFG. CO. MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF: LOCATION																											
									SANI-CEPTOR® STAINLESS STEEL FLOOR, AREA & INDIRECT WASTE DRAINS WITH 12" (304) STAINLESS STEEL SQUARE TOPS																			
WITH DOME BOTTOM STRAINER USDA ACCEPTED <table border="1" style="margin: auto;"> <thead> <tr> <th>W/Dome Strainer</th> <th>"B" DIM</th> <th>Approx Wt. Lbs.</th> <th>W/Sediment Bucket</th> </tr> </thead> <tbody> <tr><td>3001</td><td>4(100)</td><td>14</td><td>3006</td></tr> <tr><td>3002</td><td>6(150)</td><td>17</td><td>3007</td></tr> <tr><td>3003</td><td>8(205)</td><td>20</td><td>3008</td></tr> <tr><td>3004</td><td>10(255)</td><td>23</td><td>3009</td></tr> </tbody> </table> Grates w/1/2" (13) holes - Free Area 34 SQ IN (219) SQ CM Optional Grates w/1/4" (6) holes - 18 SQ IN (116) SQ CM A (Pipe Size) = 02(50), 03(75) or 04(100) Y NO-HUB Outlet WITH SEDIMENT BUCKET									W/Dome Strainer	"B" DIM	Approx Wt. Lbs.	W/Sediment Bucket	3001	4(100)	14	3006	3002	6(150)	17	3007	3003	8(205)	20	3008	3004	10(255)	23	3009
W/Dome Strainer	"B" DIM	Approx Wt. Lbs.	W/Sediment Bucket																									
3001	4(100)	14	3006																									
3002	6(150)	17	3007																									
3003	8(205)	20	3008																									
3004	10(255)	23	3009																									
FEATURES, OPTIONS AND ORDERING INFORMATION																												
REGULARLY FURNISHED: 14 Gauge Type 304 SS Receptor Body with Seepage Control Holes, Cast Type 316 SS Ribbed Non-Tilt Loose Set ADA Grate with 1/2"(13) Square Holes. Perforated SS Dome Bottom Strainer or Sediment Bucket as indicated by Figure Number. Body Rim and Grate are polished to No. 4 finish. VARIATIONS: ☐ BW Butt Weld Outlet (Specify Schedule -S05, -S10, or -S40) ☐ T Male Threaded Connection ☐ Less Seepage Control Holes -LSH ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ With Anchor Flange -F ☐ With Flange and Flashing Clamp -F-C ☐ USDA Compliant OPTIONAL MATERIALS: ☐ Drains: Fabricated from Type 316 Stainless Steel ☐ Funnel: Type 304 Stainless Steel ☐ Funnel: Type 316 Stainless Steel Bucket Models Only: ☐ With SS Dome Bottom Strainer -DBS ☐ With SS Solid Bottom Ported Bucket -SBP ☐ With Mesh Lined Bucket -BS NOTE: When determining location of this drain, consideration must be given to traffic loading factors. When used in areas where the drain is subjected to any traffic loading heavier than pedestrian foot traffic, the location, load and description of load shall be submitted to Jay R. Smith's Sales Engineering Department for evaluation and selection of proper grate.																												
OPTIONAL TOP GRATES AND COVERS																												
SUFFIX DESCRIPTION ☐ -10 Less SS Grate ☐ -12 With SS 1/2 Grate ☐ -13 With SS 3/4 Grate ☐ -14 With SS 2 1/2" (64) SQ Center Hole Grate ☐ -15 With SS Recessed Grate with Handle ☐ -18 With NB Rim and Angle ADA Grate ☐ -21 With SS Grate with 4" (100) DIA NB Funnel ☐ -22 With SS Grate with 6" (150) DIA NB Funnel ☐ -25 With SS Grate with 8 1/4(210) x 3 1/4(83) x 4 1/2"(115) High Oval NB Funnel ☐ -26 With SS Grate with 6(150) x 2 1/2(64) x 1"(25) High Oval NB Funnel ☐ -41 With SS Solid Cover ☐ -42 With SS 1/2 Solid Cover ☐ -43 With SS 3/4 Solid Cover ☐ -44 With SS 2 1/2" (64) SQ Center Hole Solid Cover SUFFIX DESCRIPTION ☐ -61 With SS Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4" (6) SQ Holes. ☐ -63 With SS Medium Duty Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4" (6) SQ Holes. ☐ -64 With SS Heavy Duty Ribbed Non-Tilt Loose Set ADA Grate with 1/2" (13) SQ Holes. ☐ -66 With SS Extra Heavy Duty Ribbed Non-Tilt Loose Set ADA Grate with 1/2" (13) SQ Holes. ☐ -68 With SS Extra Heavy Duty Ribbed Non-Tilt Loose Set 3/4 Grate with 1/2" (13) SQ Holes. ☐ -69 With 1" (25) Thick Underbolted NB Rim and Extra Heavy Duty Cast Stainless Steel Secured ADA Grate. NOTE: Dimensions shown in parentheses are in millimeters. • Flange is Located 2" (51) from Top of Drain 3" (76) When Specified																												
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:10%;">REV.</td> <td style="width:15%;">DATE</td> <td style="width:30%;">DESCRIPTION</td> <td style="width:10%;">BY</td> <td style="width:10%;">CKD. BY</td> <td style="width:10%;">WEIGHT POUNDS</td> <td style="width:10%;">VOLUME CUBIC FEET</td> <td style="width:15%; text-align: center; vertical-align: middle;"> FIGURE NUMBER 3001-Series </td> </tr> </table>									REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3001-Series												
REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 3001-Series																					



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov