

N	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION 																																						
	TILE FLOOR CLEANOUTS WITH "TWIS-TO-FLOOR®" ADJUSTABLE TOPS																																										
	SQUARE NICKEL BRONZE TOP WITH TILE RECESS																																										
TWIS-TO-FLOOR® ADJUSTMENT SPEEDI-SET® OUTLET ▲ "A" (Pipe Size) = 02(50), 03(75) or 04(100) Conforms to ASME A112.36.2/CSA B79.2																																											
<table border="0"> <tr> <td>☐</td> <td>Fig. 4171L.....Gasket Seal - ABS Plug</td> </tr> <tr> <td>☐</td> <td>Fig. 4172L.....Gasket Seal - Bronze Plug</td> </tr> <tr> <td>☐</td> <td>Fig. 4173L.....Taper Thread - Bronze Plug</td> </tr> <tr> <td>☐</td> <td>Fig. 4174L.....Taper Thread - ABS Plug</td> </tr> </table> (Twis-to-Floor® design shown with gasketed plug.) NOTE: Dimensions shown in parentheses are in millimeters.						☐	Fig. 4171L.....Gasket Seal - ABS Plug	☐	Fig. 4172L.....Gasket Seal - Bronze Plug	☐	Fig. 4173L.....Taper Thread - Bronze Plug	☐	Fig. 4174L.....Taper Thread - ABS Plug																														
☐	Fig. 4171L.....Gasket Seal - ABS Plug																																										
☐	Fig. 4172L.....Gasket Seal - Bronze Plug																																										
☐	Fig. 4173L.....Taper Thread - Bronze Plug																																										
☐	Fig. 4174L.....Taper Thread - ABS Plug																																										
REGULARLY FURNISHED: Duco Cast Iron Cleanout with Square Adjustable Secured Nickel Bronze Top with 1/8"(3) Tile Recess. Closure Plug Type as Indicated By Figure Number Selected. VARIATIONS: <table border="0"> <tr> <td>☐</td> <td>Flashing Flange -F</td> </tr> <tr> <td>☐</td> <td>Flange with Flashing Clamp -F-C</td> </tr> <tr> <td>☐</td> <td>Vandal Proof Top -U</td> </tr> </table> ▲ Available in Extra Heavy, Service Weight or NO-HUB. OPTIONAL MATERIALS: <table border="0"> <tr> <td>☐</td> <td>Galvanized Cast Iron -G</td> </tr> <tr> <td>☐</td> <td>Polished Bronze Top -PB</td> </tr> </table>						☐	Flashing Flange -F	☐	Flange with Flashing Clamp -F-C	☐	Vandal Proof Top -U	☐	Galvanized Cast Iron -G	☐	Polished Bronze Top -PB																												
☐	Flashing Flange -F																																										
☐	Flange with Flashing Clamp -F-C																																										
☐	Vandal Proof Top -U																																										
☐	Galvanized Cast Iron -G																																										
☐	Polished Bronze Top -PB																																										
FIGURE NUMBER	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10%;">N</td> <td style="width: 10%;">4-11-24</td> <td style="width: 30%;">Added ASME Note</td> <td style="width: 10%;">HS</td> <td style="width: 10%;">CL</td> <td style="width: 10%;">WEIGHT POUNDS</td> <td style="width: 10%;">VOLUME CUBIC FEET</td> <td style="width: 20%;">FIGURE NUMBER</td> </tr> <tr> <td>M</td> <td>8-16-23</td> <td>Removed Function</td> <td>HS</td> <td>CL</td> <td></td> <td></td> <td rowspan="3" style="font-size: 2em; font-weight: bold;">4171 SERIES</td> </tr> <tr> <td>L</td> <td>3-14-23</td> <td>Added ® to Speedi-Set</td> <td>KK</td> <td>CL</td> <td></td> <td></td> </tr> <tr> <td>K</td> <td>1-20-22</td> <td>Removed "C.O." cast in"</td> <td>KK</td> <td>CL</td> <td></td> <td></td> </tr> <tr> <td>REV.</td> <td>DATE</td> <td>DESCRIPTION</td> <td>BY</td> <td>CKD. BY</td> <td></td> <td></td> <td></td> </tr> </table>					N	4-11-24	Added ASME Note	HS	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER	M	8-16-23	Removed Function	HS	CL			4171 SERIES	L	3-14-23	Added ® to Speedi-Set	KK	CL			K	1-20-22	Removed "C.O." cast in"	KK	CL			REV.	DATE	DESCRIPTION	BY	CKD. BY			
	N	4-11-24	Added ASME Note	HS	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER																																			
M	8-16-23	Removed Function	HS	CL			4171 SERIES																																				
L	3-14-23	Added ® to Speedi-Set	KK	CL																																							
K	1-20-22	Removed "C.O." cast in"	KK	CL																																							
REV.	DATE	DESCRIPTION	BY	CKD. BY																																							

D	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION																													
	TILE FLOOR CLEANOUTS WITH "TWIS-TO-FLOOR®" ADJUSTABLE TOPS																																	
	SQUARE NICKEL BRONZE TOP WITH TILE RECESS																																	
▲ SPEEDI-SET® OUTLET ▲ "A" (Pipe Size) = 06(150) & 08(200) Conforms to ASME A112.36.2/CSA B79.2 ▲ SPEEDI-SET® OUTLET -L Service Weight - For Service Weight and No Hub Cast Iron Pipe (Available for all pipe sizes) -LXH Extra Heavy - For Extra Heavy Cast Iron Pipe (Available for all pipe sizes) -LXH Extra Heavy - For PVC Pipe (Available for 2", 3", 4", and 8" pipe sizes only) -LPVC Plastic Pipe - For PVC or ABS pipe (Available for 6" pipe size only) * This Dimension to Internal Stop of Speedi-Set® Gasket. ** When Flange-F is specified Min. 1 1/8 (29) becomes 1 5/8 (41)																																		
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 20%;">A SIZE</th> <th style="width: 20%;">B</th> <th style="width: 20%;">C</th> </tr> </thead> <tbody> <tr> <td>06(150)</td> <td>*3(76)</td> <td>4 9/16(117)</td> </tr> <tr> <td>08(200)</td> <td>*3 1/4(83)</td> <td>4 13/16(121)</td> </tr> </tbody> </table>						A SIZE	B	C	06(150)	*3(76)	4 9/16(117)	08(200)	*3 1/4(83)	4 13/16(121)																				
A SIZE	B	C																																
06(150)	*3(76)	4 9/16(117)																																
08(200)	*3 1/4(83)	4 13/16(121)																																
"TWIS-TO-FLOOR®" ADJUSTMENT SPEEDI-SET® OUTLET ▲ ☐ Fig. 4173L.....Taper Thread - Bronze Plug																																		
REGULARLY FURNISHED: Duco Cast Iron Cleanout with Taper Thread Bronze Plug and Square Adjustable Secured Nickel Bronze Top with 1/8 (3) Tile Recess. VARIATIONS: ☐ Flashing Flange -F ☐ Flange with Flashing Clamp -F-C ☐ Vandal Proof Top -U OPTIONAL MATERIALS: ☐ Galvanized Cast Iron -G ☐ Polished Bronze Top -PB																																		
NOTE: Dimensions shown in parentheses are in millimeters.																																		
FIGURE NUMBER	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 20px;">D</td><td>4-11-24</td><td rowspan="4" style="text-align: center; vertical-align: middle;">Added ASME Note Removed Function Added ® to Speedi-Set Rev./Added New ▲Note</td> <td style="width: 20px;">HS</td><td rowspan="4" style="text-align: center; vertical-align: middle;">CL</td> <td rowspan="4" style="width: 40px;">WEIGHT POUNDS</td> <td rowspan="4" style="width: 40px;">VOLUME CUBIC FEET</td> <td rowspan="4" style="width: 100px; text-align: center; vertical-align: middle;">FIGURE NUMBER 4173</td> </tr> <tr> <td>C</td><td>8-16-23</td> <td>HS</td> <td>CL</td> </tr> <tr> <td>B</td><td>3-14-23</td> <td>KS</td><td>CL</td> </tr> <tr> <td>A</td><td>10-9-2020</td> <td>MW</td><td>CR</td> </tr> </table>		D	4-11-24	Added ASME Note Removed Function Added ® to Speedi-Set Rev./Added New ▲Note	HS	CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 4173	C	8-16-23	HS	CL	B	3-14-23	KS	CL	A	10-9-2020	MW	CR	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 40px;">REV.</td> <td style="width: 40px;">DATE</td> <td style="width: 40px;">DESCRIPTION</td> <td style="width: 40px;">BY</td> <td style="width: 40px;">CKD. BY</td> </tr> <tr> <td> </td> <td> </td> <td> </td> <td> </td> <td> </td> </tr> </table>		REV.	DATE	DESCRIPTION	BY	CKD. BY					
	D	4-11-24	Added ASME Note Removed Function Added ® to Speedi-Set Rev./Added New ▲Note	HS		CL					WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 4173																					
C	8-16-23	HS		CL																														
B	3-14-23	KS		CL																														
A	10-9-2020	MW		CR																														
REV.	DATE	DESCRIPTION	BY	CKD. BY																														