

M	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF:				LOCATION 																																							
	CAULK FERRULE CLEANOUTS WITH ACCESS COVERS																																											
DRAWING NUMBER S4420	SIZE A	SCALE: NONE	DATE: 2-16-70	APPROVED BY: BH	CHECKED BY: BH	DRAWN BY: RK	TAPER THREAD PLUG WITH ROUND COVER																																					
				1/4(6) - 20 x 2 1/2(64) Long Flat Head Machine Screw 1/4(6) - 20 x 1 1/2(38) Long Flat Head Machine Screw																																								
WITH COUNTERSUNK PLUG ☐ FIG. 4420C LESS COVER AND SCREW ☐ FIG. 4421C WITH DEEP COVER AND SCREW ☐ FIG. 4422C WITH SHALLOW COVER AND SCREW																																												
Conforms to ASME A112.36.2/CSA B79.2																																												
<table border="1" style="border-collapse: collapse; width: 100%;"> <thead> <tr> <th></th> <th>A SIZE</th> <th>B DIA</th> <th>C SIZE</th> <th>D</th> <th>E DIA</th> </tr> </thead> <tbody> <tr> <td>▲ 02 (50)</td> <td>4 1/4 (110)</td> <td>1 1/2 (38)</td> <td>3 1/2 (89)</td> <td>*7 1/4 (185)</td> </tr> <tr> <td>▲ 03 (80)</td> <td>5 1/2 (140)</td> <td>2 1/2 (64)</td> <td>3 3/4 (95)</td> <td>*7 1/4 (185)</td> </tr> <tr> <td>▲ 04 (100)</td> <td>5 1/2 (140)</td> <td>3 1/2 (89)</td> <td>4 1/4 (110)</td> <td>*7 1/4 (185)</td> </tr> <tr> <td>05 (125)</td> <td>7 (180)</td> <td>4 (100)</td> <td>4 1/4 (110)</td> <td>*7 1/4 (185)</td> </tr> <tr> <td>06 (150)</td> <td>9 1/4 (235)</td> <td>5 (125)</td> <td>4 1/4 (110)</td> <td>9 1/4 (235)</td> </tr> <tr> <td>08 (200)</td> <td>11 1/4 (285)</td> <td>6 (150)</td> <td>4 1/2 (115)</td> <td>11 1/4 (285)</td> </tr> </tbody> </table> * = Die Formed SS Cover Only.										A SIZE	B DIA	C SIZE	D	E DIA	▲ 02 (50)	4 1/4 (110)	1 1/2 (38)	3 1/2 (89)	*7 1/4 (185)	▲ 03 (80)	5 1/2 (140)	2 1/2 (64)	3 3/4 (95)	*7 1/4 (185)	▲ 04 (100)	5 1/2 (140)	3 1/2 (89)	4 1/4 (110)	*7 1/4 (185)	05 (125)	7 (180)	4 (100)	4 1/4 (110)	*7 1/4 (185)	06 (150)	9 1/4 (235)	5 (125)	4 1/4 (110)	9 1/4 (235)	08 (200)	11 1/4 (285)	6 (150)	4 1/2 (115)	11 1/4 (285)
	A SIZE	B DIA	C SIZE	D	E DIA																																							
▲ 02 (50)	4 1/4 (110)	1 1/2 (38)	3 1/2 (89)	*7 1/4 (185)																																								
▲ 03 (80)	5 1/2 (140)	2 1/2 (64)	3 3/4 (95)	*7 1/4 (185)																																								
▲ 04 (100)	5 1/2 (140)	3 1/2 (89)	4 1/4 (110)	*7 1/4 (185)																																								
05 (125)	7 (180)	4 (100)	4 1/4 (110)	*7 1/4 (185)																																								
06 (150)	9 1/4 (235)	5 (125)	4 1/4 (110)	9 1/4 (235)																																								
08 (200)	11 1/4 (285)	6 (150)	4 1/2 (115)	11 1/4 (285)																																								
▲ Sized for Service Weight and/or NO-HUB																																												
REGULARLY FURNISHED: Duco Cast Iron Caulk Ferrule with Cast Bronze Taper Thread Plug. Type of Cover as Indicated by Figure Number Selected. VARIATIONS: ☐ Longer Screw 6"(150) Lg. -LS ☐ "T" Handle Plug -TH Plug Tapped 1/4"(6) -20 Thread ☐ Vandal Proof Screw-U OPTIONAL MATERIALS: (4421) ☐ Nickel Bronze Deep Cover -NB 9 1/4"(235) & 11 1/4"(285) sizes only ☐ Polished Bronze Deep Cover -PB 9 1/4"(235) & 11 1/4"(285) sizes only																																												
NOTE: Dimensions shown in parentheses are in millimeters.																																												
FIGURE NUMBER 4420 SERIES	M L K J 9-23-24 4-11-24 2-28-24 8-18-23	Revised Optional Materials Added ASME Note Revised Optional Materials Removed Function	HS HS HS HS HS HS	CL CL CL CL CL CL	WEIGHT POUNDS VOLUME CUBIC FEET	FIGURE NUMBER 4420 SERIES																																						
REV.	DATE	DESCRIPTION	BY	CKD. BY																																								



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov