

L	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION
	CAULK FERRULE CLEANOUTS WITH FRAME AND COVER				
DRAWING NUMBER	S4438				
SIZE	A				
SCALE:	NONE				
DATE:	4-11-83				
APPROVED BY:	SJM				
CHECKED BY:	SJM				
DRAWN BY:	CR				
4438, 4439					
FIGURE NUMBER	4438, 4439				

LEAD SEAL PLUG WITH FRAME AND SCORIATED COVER

FIG. 4438C FACE-OF-WALL COVER

FIG. 4439C FLUSH-WITH-WALL COVER

A SIZE	B OPENING		C SIZE	D	E DIA	F SQ	G SQ
	DIA	SQ					
02 (50)	4 (100)	6 x 6 (150) x (150)	1 1/2 (38)	2 1/2 (64)	4 1/2 (115)	7 (180)	5 1/2 (140)
03 (75)	5 1/2 (140)	6 x 6 (150) x (150)	2 1/2 (64)	2 3/4 (70)	5 3/4 (145)	7 (180)	5 1/2 (140)
04 (100)	6 (150)	6 x 6 (150) x (150)	3 1/2 (89)	3 (76)	6 1/2 (165)	7 (180)	5 1/2 (140)
06 (150)	8 (205)	8 x 8 (205) x (205)	5 1/2 (140)	3 (76)	8 1/2 (215)	9 (230)	7 1/2 (190)

REGULARLY FURNISHED:

Duco Cast Iron Caulk Ferrule with Cast Iron Lead Seal Plug and Secured Scoriated Nickel Bronze Cover and Frame with Anchor Lugs. Type of Cover as Indicated by Figure Number Selected.

VARIATIONS:

☐ Cover Drilled in Center and Furnished with 1/4"(6)-20 x 2 1/2"(64) Long Screw

☐ "T" Handle Plug -TH Plug Tapped 1/4"(6) -20 Thread

☐ Vandal Proof Screws-U

OPTIONAL MATERIALS:

☐ Cast Bronze Plug -BP

☐ Polished Bronze Frame and Cover -PB

NOTE: Dimensions shown in parentheses are in millimeters.

L K J H	10-11-24 2-28-24 8-18-23 10-7-14	Revised Table Revised Optional Materials Removed Function Revised Variations
REV.	DATE	DESCRIPTION

HS HS HS TBW	CL CL CL BW
BY	CKD. BY

WEIGHT POUNDS	VOLUME CUBIC FEET

FIGURE NUMBER

4438, 4439



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov