

F	SMITH® JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION			
	1/4 TURN QUARTERHORSE WARM CLIMATE WALL HYDRANT							
DRAWING NUMBER 5560QT (-SAP-H-WH) 5561QT (-SAP-H-WH)	SIZE A	BRONZE BOX TYPE "TWIN-TEMP" FOR HOT AND COLD WATER						
FRONT VIEW SIDE VIEW ☐ Fig. 5560QT-SAP 1/2"(13) FEMALE & 3/4"(19) MALE INLET ☐ Fig. 5561QT-SAP 1"(25) MALE NPT INLET* * When specifying a 5561QT-SAP add 3/4"(19) to length of inlet connection as shown above. Installer is responsible for providing a 100% watertight positive seal at the hydrant to box interface and hydrant to wall interface. Seal all interior joints, seams, gasket seams/closures including around the hydrant box flange with an appropriate sealant recommended by a sealant manufacturer. NOTE: Jay R. Smith does not warrant the performance or life expectancy of the sealant material.								
REGULARLY FURNISHED: Bronze Quarter Turn "Twin-Temp" Hydrant with hose Connection, "T" Handle Key and Bronze Box with Chrome Plated Face. Inlet Size Furnished as Indicated by Figure Number Selected. VARIATIONS: ☐ Cylinder Lock -CL ☐ 1"(25) Hose Connection -HC1 ☐ 3/4"(19) Vacuum Breaker (Self Draining Type) -H ☐ Wheel Handle -WH ☐ "Water" Cast On Cover -W ☐ (2) 3/8"(10) Tappings -TAP OPTIONAL MATERIALS: ☐ Nickel Bronze Box -NB ☐ Polished Bronze Hydrant -PB ☐ Rough Bronze Box -RB								
NOTES: 1. Recommended Wall Opening 9 3/4"(250) x 9 3/4"(250).** 2. All Jay R. Smith hydrants are manufactured with "NO-LEAD" brazing rings and USDA approved lubricants. 3. The AB100, AB1953, California Lead Law, and NSF/ANSI Standard 61 - Drinking Water System Components are not applicable to Jay R. Smith hydrants as they do not convey/dispense water for human consumption through drinking or cooking. 4. When vacuum breaker is supplied the hose must be removed to allow draining to prevent freezing. 5. Dimensions shown in parentheses are in millimeters. 6. FOR IRRIGATION PURPOSES ONLY.								
FIGURE NUMBER 5560QT (-SAP-H-WH) 5561QT (-SAP-H-WH)	REV. F E D C	DATE 8-1-23 3-22-23 3-8-23 10-16-18	DESCRIPTION Removed Function Revised Note 3 Added -TAP to Variations Rev. Reg. Furn., Variations	BY HS KK KB TBW	CKD. BY CL JT CL CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 5560QT (-SAP-H-WH) 5561QT (-SAP-H-WH)



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov