

H	JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:					LOCATION 		
	MILD CLIMATE ANTI-SIPHON SILLCOCK BOX TYPE WITH CONCEALED HOSE CONNECTION							
DRAWING NUMBER s5572, 5573	SIZE A	SCALE: NONE	DATE: 7-7-11	APPROVED BY: CL	CHECKED BY: CL	DRAWN BY: TBW	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE	
A (Inlet Size) = 1/2(13) or 3/4(19) Fig. 5572 1/2"(13) Female NPT Inlet Fig. 5573 3/4"(19) Female NPT Inlet								
NOTES: - Recommended wall opening 9 3/4"(250) x 6"(150). - The AB100, AB1953, California Lead Law, and NSF/ANSI Standard 61 - Drinking Water Components are not applicable to Jay R. Smith hydrants as they do not convey/dispense water for human consumption through drinking or cooking. - Dimensions shown in parentheses are in millimeters. FOR IRRIGATION PURPOSES ONLY.								
REGULARLY FURNISHED: Hose Valve has a Rough Finish Brass Body Removable Wheel Handle, "T" Handle Key, NPT Female Threaded Inlet Size Indicated by Figure Number Selected, ASSE 1011 Vacuum Breaker with 3/4"(19) Hose Connection and Stainless Steel Box with Full 180° Cover Opening. VARIATIONS: Dual Check Valve -BFP (2) 3/8"(10) Tappings -TAP Cylinder Lock -CL								
Installer is responsible for providing a 100% watertight positive seal at the hydrant to box interface and hydrant to wall interface. Seal all interior joints, seams, gasket seams/closures including around the hydrant box flange with an appropriate sealant recommended by a sealant manufacturer. NOTE: Jay R. Smith does not warrant the performance or life expectancy of the sealant material.								
FIGURE NUMBER 5572, 5573	H G F E	9-5-23 8-1-23 3-22-23 3-8-23	Added -CL to Variations Removed Function Revised Note 2 Added -TPS to Variations	HS HS KK KK	CL CL JT CL	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 5572, 5573
	REV.	DATE	DESCRIPTION	BY	CKD. BY			