

L	SMITH JAY R. SMITH MFG. CO. MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION																																																						
	GUTTER DRAINS																																																										
FIGURE NUMBER 6200	DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE																																																										
	DRAWING NUMBER S6200																																																										
SIZE A																																																											
SCALE: NONE																																																											
DATE: 4-5-83																																																											
APPROVED BY: SJM																																																											
CHECKED BY: DT																																																											
DRAWN BY: BS																																																											
A (Pipe Size) = 0150(40), 02(50) or **0250(65) THREADED OUTLET ONLY THREADED OUTLET ONLY <table border="1" style="width: 100%; font-size: 0.8em;"> <thead> <tr> <th>Fig. No.</th> <th>B</th> <th>C</th> <th>D</th> <th>E</th> <th>Free Area</th> </tr> </thead> <tbody> <tr> <td>6250T</td> <td>4(100)</td> <td>2 3/4(70)</td> <td>1 1/4(32)</td> <td>3 1/4(83)</td> <td>3.4 SQ IN (22) SQ CM</td> </tr> <tr> <td>6270T</td> <td>5 1/4(135)</td> <td>2(51)</td> <td>2(51)</td> <td>3 1/4(83)</td> <td>4.8 SQ IN (31) SQ CM</td> </tr> </tbody> </table> **0250(65) Outlet available with Fig. 6270 only. <table border="1" style="width: 100%; font-size: 0.8em;"> <thead> <tr> <th>Fig. No.</th> <th>"A" Size</th> <th>B</th> <th>C</th> <th>D</th> <th>Free Area</th> </tr> </thead> <tbody> <tr> <td>6205T</td> <td>01(25), 0150(40), 02(50)</td> <td>3 3/4(95)</td> <td>2 1/4(57)</td> <td>2 9/16(65)</td> <td>2.7 SQ IN(17) SQ CM</td> </tr> <tr> <td>6210T</td> <td>02(50), 0250(65), 03(75)</td> <td>5 9/16(141)</td> <td>2 13/16(71)</td> <td>2 15/16(75)</td> <td>4.8 SQ IN(31) SQ CM</td> </tr> <tr> <td>*6225T</td> <td>0150(40), 02(50)</td> <td>10 1/8(257)</td> <td>2 3/8(60)</td> <td>3 3/16(81)</td> <td>5.8 SQ IN(37) SQ CM</td> </tr> <tr> <td>6230T</td> <td>02(50), 0250(65), 03(75)</td> <td>12 1/16(306)</td> <td>4(100)</td> <td>Δ 2 1/2(65)</td> <td>11.3 SQ IN(73) SQ CM</td> </tr> <tr> <td>6230T</td> <td>04(100)</td> <td>12 1/8(308)</td> <td>4 1/8(105)</td> <td>Δ 2 1/2(65)</td> <td>11.3 SQ IN(73) SQ CM</td> </tr> </tbody> </table> ΔFor Figure No. 6230 only; when specifying NB, PB or CP add 3/8(10) to "D" dimension *Anchor flange variations available with figure no. 6225 only. REGULARLY FURNISHED: Duco Cast Iron Body with Secured Chrome Plated Bronze Face. VARIATIONS: ☐ *Anchor Flange -F ☐ NO-HUB Adaptor (Specify Fig. 2646Y) 2(50), 3(75) and 4"(100) Only ☐ Vandal Proof Screws -U OPTIONAL MATERIALS: ☐ Bronze Body -BB ☐ Galvanized Cast Iron -G ☐ Nickel Bronze Face -NB ☐ Polished Bronze Face -PB ☐ Stainless Steel (Fig. 6230 only) (Specify Fig. 9745) NOTE: This product does not conform to or meet the requirements of ASME Standard No. A112.19.8-2007, titled "Suction Fittings for Use in Swimming Pools, Wading Pools, Spas, and Hot Tubs." This product shall not be used in any installation in swimming pools, wading pools, spas, hot tubs as well as other aquatic facilities. Due to the potential endangerment from arduous and forceful suction, entrapment or entanglement regardless of whether it is hair, head, limbs or other body parts, this product is prohibited from installation in these applications. NOTE: Dimensions shown in parentheses are in millimeters.						Fig. No.	B	C	D	E	Free Area	6250T	4(100)	2 3/4(70)	1 1/4(32)	3 1/4(83)	3.4 SQ IN (22) SQ CM	6270T	5 1/4(135)	2(51)	2(51)	3 1/4(83)	4.8 SQ IN (31) SQ CM	Fig. No.	"A" Size	B	C	D	Free Area	6205T	01(25), 0150(40), 02(50)	3 3/4(95)	2 1/4(57)	2 9/16(65)	2.7 SQ IN(17) SQ CM	6210T	02(50), 0250(65), 03(75)	5 9/16(141)	2 13/16(71)	2 15/16(75)	4.8 SQ IN(31) SQ CM	*6225T	0150(40), 02(50)	10 1/8(257)	2 3/8(60)	3 3/16(81)	5.8 SQ IN(37) SQ CM	6230T	02(50), 0250(65), 03(75)	12 1/16(306)	4(100)	Δ 2 1/2(65)	11.3 SQ IN(73) SQ CM	6230T	04(100)	12 1/8(308)	4 1/8(105)	Δ 2 1/2(65)	11.3 SQ IN(73) SQ CM
Fig. No.	B	C	D	E	Free Area																																																						
6250T	4(100)	2 3/4(70)	1 1/4(32)	3 1/4(83)	3.4 SQ IN (22) SQ CM																																																						
6270T	5 1/4(135)	2(51)	2(51)	3 1/4(83)	4.8 SQ IN (31) SQ CM																																																						
Fig. No.	"A" Size	B	C	D	Free Area																																																						
6205T	01(25), 0150(40), 02(50)	3 3/4(95)	2 1/4(57)	2 9/16(65)	2.7 SQ IN(17) SQ CM																																																						
6210T	02(50), 0250(65), 03(75)	5 9/16(141)	2 13/16(71)	2 15/16(75)	4.8 SQ IN(31) SQ CM																																																						
*6225T	0150(40), 02(50)	10 1/8(257)	2 3/8(60)	3 3/16(81)	5.8 SQ IN(37) SQ CM																																																						
6230T	02(50), 0250(65), 03(75)	12 1/16(306)	4(100)	Δ 2 1/2(65)	11.3 SQ IN(73) SQ CM																																																						
6230T	04(100)	12 1/8(308)	4 1/8(105)	Δ 2 1/2(65)	11.3 SQ IN(73) SQ CM																																																						
REV.	DATE	DESCRIPTION	BY	CKD. BY	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 6200																																																				



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov