

Y	JAY R. SMITH MFG. CO. MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 888-377-7818 www.jrsmith.com						LOCATION																																																								
	14 GAGE STAINLESS STEEL FLOOR, AREA & INDIRECT WASTE DRAINS WITH 12" (304) SQUARE TOP																																																														
	DRAWING NUMBER S9691		SIZE A		SCALE: NONE		DATE: 5-4-82																																																								
	WE CAN ASSUME NO RESPONSIBILITY FOR USE OF SUPERSEDED OR VOID DATA																																																														
With Dome Bottom Strainer USDA ACCEPTED FIGURE NUMBERS <table border="1" style="margin: auto;"> <thead> <tr> <th>W/Dome Strainer</th> <th>"B" Dim.</th> <th>Approx. Wt. Lbs.</th> <th>W/Sediment Bucket</th> </tr> </thead> <tbody> <tr><td>9691</td><td>4 (100)</td><td>14</td><td>9696</td></tr> <tr><td>9692</td><td>6 (150)</td><td>17</td><td>9697</td></tr> <tr><td>9693</td><td>8 (205)</td><td>20</td><td>9698</td></tr> <tr><td>9694</td><td>10 (255)</td><td>23</td><td>9699</td></tr> </tbody> </table> Grates w/1/2"(13) holes - Free Area 34 SQ IN (219) SQ CM Optional grates w/1/4"(6) holes - Free Area 18 SQ IN (116) SQ CM A (Pipe Size) = 02(50), 03(75) or 04(100) Y NO-HUB Outlet Regular Schedule 40 Regularly Furnished With Sediment Bucket								W/Dome Strainer	"B" Dim.	Approx. Wt. Lbs.	W/Sediment Bucket	9691	4 (100)	14	9696	9692	6 (150)	17	9697	9693	8 (205)	20	9698	9694	10 (255)	23	9699																																				
W/Dome Strainer	"B" Dim.	Approx. Wt. Lbs.	W/Sediment Bucket																																																												
9691	4 (100)	14	9696																																																												
9692	6 (150)	17	9697																																																												
9693	8 (205)	20	9698																																																												
9694	10 (255)	23	9699																																																												
FEATURES, OPTIONS AND ORDERING INFORMATION																																																															
REGULARLY FURNISHED: 14 Gage Type 304 SS Receptor Body with "Seepage Control Holes", Cast Type 316 SS Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Square Holes. Perforated SS Dome Bottom Strainer or Sediment Bucket as Indicated by Figure Number.																																																															
VARIATIONS: ☐ Dome Bottom Strainer -DBS (Bucket Models only) ☐ Less Seepage Control Holes -LSH ☐ Solid Ported Bucket -SBP ☐ With Anchor Flange -F ☐ With Flange and Flashing Clamp -F-C ☐ Trap Primer Connection -P050 1/2"(13) & -P075 3/4"(19) ☐ BW Butt Weld Outlet (Specify Schedule -S05, -S10 or -S40) ☐ T Male Threaded Connection ☐ USDA Compliant BUCKET MODELS ONLY: ☐ With SS Solid Bottom Ported Bucket -SBP ☐ With SS Dome Bottom Strainer -DBS OPTIONAL MATERIALS: ☐ Fabricated from Type 316 Stainless Steel -316																																																															
C File No. 3663																																																															
NOTE: When determining location of this drain, consideration must be given to traffic loading factors. When used in areas where the drain is subjected to any traffic loading heavier than pedestrian foot traffic, the location, load and description of load shall be submitted to Jay R. Smith's Sales Engineering Department for evaluation and selection of proper grate.																																																															
OPTIONAL TOP GRATES AND COVERS																																																															
<table style="width: 100%;"> <thead> <tr> <th style="width: 10%;">Suffix</th> <th style="width: 80%;">Description</th> <th style="width: 10%;">Suffix</th> <th style="width: 80%;">Description</th> </tr> </thead> <tbody> <tr> <td>☐ -10</td> <td>Less SS Grate</td> <td>☐ -61</td> <td>With SS Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4"(6) Sq. Holes - Certified Light Duty</td> </tr> <tr> <td>☐ -12</td> <td>With SS 1/2 Grate</td> <td>☐ -63</td> <td>With SS Medium Duty Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4"(6) Sq. Holes - Certified Medium Duty</td> </tr> <tr> <td>☐ -13</td> <td>With SS 3/4 Grate</td> <td>☐ -64</td> <td>With SS Heavy Duty Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Sq. Holes</td> </tr> <tr> <td>☐ -14</td> <td>With SS 2 1/2(64) Sq. Center Hole Grate</td> <td>☐ -66</td> <td>With SS Extra Heavy Duty Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Sq. Holes - Certified Extra Heavy Duty</td> </tr> <tr> <td>☐ -15</td> <td>With SS Recessed Grate with Handle</td> <td>☐ -69</td> <td>With 1"(25) Thick Under bolted NB Rim and Extra Heavy Duty Cast Stainless Steel Secured Grate (Flange Regularly Furnished 2"(51) from top will become 3"(76) from top) Certified Extra Heavy Duty</td> </tr> <tr> <td>☐ -21</td> <td>With SS Grate with 4"(100) Dia. SS Funnel</td> <td></td> <td></td> </tr> <tr> <td>☐ -22</td> <td>With SS Grate with 6"(150) Dia. SS Funnel</td> <td></td> <td></td> </tr> <tr> <td>☐ -25</td> <td>With SS Grate with 8 1/4(210) x 3 1/4(53) x 4 1/2"(115) High Oval SS Funnel</td> <td></td> <td></td> </tr> <tr> <td>☐ -26</td> <td>With SS Grate with 6(150) x 2 1/2(64) x 1"(25) High Oval SS Funnel</td> <td></td> <td></td> </tr> <tr> <td>☐ -41</td> <td>With SS Solid Cover</td> <td></td> <td></td> </tr> <tr> <td>☐ -42</td> <td>With SS 1/2 Solid Cover</td> <td></td> <td></td> </tr> <tr> <td>☐ -43</td> <td>With SS 3/4 Solid Cover</td> <td></td> <td></td> </tr> <tr> <td>☐ -44</td> <td>With SS 2 1/2"(64) Sq. Center Hole Solid Cover</td> <td></td> <td></td> </tr> </tbody> </table>								Suffix	Description	Suffix	Description	☐ -10	Less SS Grate	☐ -61	With SS Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4"(6) Sq. Holes - Certified Light Duty	☐ -12	With SS 1/2 Grate	☐ -63	With SS Medium Duty Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4"(6) Sq. Holes - Certified Medium Duty	☐ -13	With SS 3/4 Grate	☐ -64	With SS Heavy Duty Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Sq. Holes	☐ -14	With SS 2 1/2(64) Sq. Center Hole Grate	☐ -66	With SS Extra Heavy Duty Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Sq. Holes - Certified Extra Heavy Duty	☐ -15	With SS Recessed Grate with Handle	☐ -69	With 1"(25) Thick Under bolted NB Rim and Extra Heavy Duty Cast Stainless Steel Secured Grate (Flange Regularly Furnished 2"(51) from top will become 3"(76) from top) Certified Extra Heavy Duty	☐ -21	With SS Grate with 4"(100) Dia. SS Funnel			☐ -22	With SS Grate with 6"(150) Dia. SS Funnel			☐ -25	With SS Grate with 8 1/4(210) x 3 1/4(53) x 4 1/2"(115) High Oval SS Funnel			☐ -26	With SS Grate with 6(150) x 2 1/2(64) x 1"(25) High Oval SS Funnel			☐ -41	With SS Solid Cover			☐ -42	With SS 1/2 Solid Cover			☐ -43	With SS 3/4 Solid Cover			☐ -44	With SS 2 1/2"(64) Sq. Center Hole Solid Cover		
Suffix	Description	Suffix	Description																																																												
☐ -10	Less SS Grate	☐ -61	With SS Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4"(6) Sq. Holes - Certified Light Duty																																																												
☐ -12	With SS 1/2 Grate	☐ -63	With SS Medium Duty Heel-Proof Ribbed Non-Tilt Loose Set Grate with 1/4"(6) Sq. Holes - Certified Medium Duty																																																												
☐ -13	With SS 3/4 Grate	☐ -64	With SS Heavy Duty Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Sq. Holes																																																												
☐ -14	With SS 2 1/2(64) Sq. Center Hole Grate	☐ -66	With SS Extra Heavy Duty Ribbed Non-Tilt Loose Set Grate with 1/2"(13) Sq. Holes - Certified Extra Heavy Duty																																																												
☐ -15	With SS Recessed Grate with Handle	☐ -69	With 1"(25) Thick Under bolted NB Rim and Extra Heavy Duty Cast Stainless Steel Secured Grate (Flange Regularly Furnished 2"(51) from top will become 3"(76) from top) Certified Extra Heavy Duty																																																												
☐ -21	With SS Grate with 4"(100) Dia. SS Funnel																																																														
☐ -22	With SS Grate with 6"(150) Dia. SS Funnel																																																														
☐ -25	With SS Grate with 8 1/4(210) x 3 1/4(53) x 4 1/2"(115) High Oval SS Funnel																																																														
☐ -26	With SS Grate with 6(150) x 2 1/2(64) x 1"(25) High Oval SS Funnel																																																														
☐ -41	With SS Solid Cover																																																														
☐ -42	With SS 1/2 Solid Cover																																																														
☐ -43	With SS 3/4 Solid Cover																																																														
☐ -44	With SS 2 1/2"(64) Sq. Center Hole Solid Cover																																																														
• Flange is located 2" (51) from top of drain. 3"(76) when specified. NOTE: Dimensions shown in parentheses are in millimeters.																																																															
Y X W V		8-24-23 2-23-23 2-18-23 12-13-21		Removed Function Added "®" Revised Variations Added ASME and CSA numbers		HS KK KK KK		CL CL CL CL																																																							
REV.		DATE		DESCRIPTION		BY		CKD. BY																																																							
9691 SERIES		DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE AND CHANGE WITHOUT NOTICE		DRAWN BY: C.R.		CHECKED BY: K.H.		APPROVED BY: J.M.																																																							
FIGURE NUMBER		9691 SERIES																																																													