

D	 SMITH® CUSTOMER DRIVEN SINCE 1926 JAY R. SMITH MFG. CO.® MEMBER OF MORRIS GROUP INTERNATIONAL POST OFFICE BOX 3237 MONTGOMERY, ALABAMA 36109-0237 (USA) TEL: 334-277-8520 FAX: 334-272-7396 www.jrsmith.com MEMBER OF: MEMBER OF: MEMBER OF:				LOCATION 			
	9812-LC FRAME AND GRATE SYSTEM							
DRAWING NUMBER a9812-LC SIZE A SCALE: NONE DATE: 8-02-2008 APPROVED BY: PJ CHECKED BY: PJ DRAWN BY: RN	"TOP VIEW CAST IRON SLOTTED GRATE SHOWN"							
	SECTION VIEW OF FRAME							
	REGULARLY FURNISHED: Powder Coated Welded Steel Frame Support System with Concrete Anchors (One Pair Every 18 Inches). Supplied with Secured Specified Grate. OPTIONAL FRAME MATERIAL: Stainless Steel (304) Galvanized Steel							
VARIATIONS: End Frame Heavy Duty, DIN 19580 Class C -56,000 lbs -1,162 psi for commercial pneumatic tire traffic patterns, forklifts and tractor trailers. 9812 -CI Slotted Cast Iron Grate 61.25 SQ IN 9812 -G Galvanized Bar Grate 263.5 SQ IN 9812 -SS (Type 304) Stainless Steel Bar Grate 263.5 SQ IN Extra Heavy Duty, DIN 19580 Class E -135,000 lbs -2,788 psi for commercial solid tire traffic pattern, forklifts and impacts from steel struts or metal wheels. 9812 -M Slotted Ductile Iron Grate 61.25 SQ IN 9812 -MADA Ductile Iron ADA Grate 42.00 SQ IN								
SMITH® ACO Trench Drain Series								
FIGURE NUMBER 	REV. 	DATE 	DESCRIPTION 	BY 	CKD. BY 	WEIGHT POUNDS 	VOLUME CUBIC FEET 	FIGURE NUMBER 9812-LC



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov